


Os acoplamentos GEKA , são acoplamentos simétricos para água e utilização geral

Material	Distancia entre garras	Temp.	Pressão Nominal
Bronze	40mm	até 95°C.	20 bar (max 50 bar)

GEKA-01	N/Referência	DN	Larg. (b)	Alt. (h)	Peso g.	ESPIGA
	GEKA01-10	3/8"	53,5	50	93	
	GEKA01-13	1/2"	53,5	50	94	
	GEKA01-16	5/8"	53,5	54	102	
	GEKA01-20	3/4"	53,5	54	102	
	GEKA01-25	1"	53,5	60	123	
	GEKA01-32	1-1/4"	53,5	70	176	
	GEKA01-40	1-1/2"	53,5	73	206	

GEKA-02	N/Referência	Rosca	Larg. (b)	Alt. (h)	Peso g.	FEMEA
	GEKA02-06	1/4"	53,5	30	86	
	GEKA02-10	3/8"	53,5	31	92	
	GEKA02-13	1/2"	53,5	31	94	
	GEKA02-20	3/4"	53,5	32	96	
	GEKA02-25	1"	53,5	33	100	
	GEKA02-32	1-1/4"	53,5	38	128	
	GEKA02-40	1-1/2"	53,5	39	135	

GEKA-03	N/Referência	Rosca	Larg. (b)	Alt. (h)	Peso g.	MACHO
	GEKA03-06	1/4"	53,5	32	89	
	GEKA03-10	3/8"	53,5	32	83	
	GEKA03-13	1/2"	53,5	32	88	
	GEKA03-20	3/4"	53,5	32	90	
	GEKA03-25	1"	53,5	32	92	
	GEKA03-32	1-1/4"	53,5	36	110	
	GEKA03-40	1-1/2"	53,5	36	135	

GEKA-04	N/Referência	Larg. (b)	Alt. (h)	Peso g.
	GEKA04	53,5	37	103

GEKA-05	N/Referência			
	GEKA05	NBR		VEDANTE